



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 1 of 11

1. Product and Company Identification

Product Name: Transparent Fence Stain

Product Code / Color:

809501 - Cedar Tone	809502 - Harvest Brown	809503 - Leatherwood
809504 - Oxford Brown	809505 - Saddle Tan	809506 - Bright Cedar
809507 - Redwood	809509 - Clear Glow	809510 - Sequoia

Recommended Use: Paint or related materials.

Company Identification:
STANDARD PAINTS, INC.
940 S. 6th Avenue
Mansfield, Texas 76063

Information Phone: 1-817-477-5060
CHEMTREC Emergency Phone: 1-800-424-9300

2. Hazard(s) Identification



Hazards of Product

Signal Word: **DANGER**

Flammable Liquid	Category	3	
Aspiration Hazard	Category	1	
Skin Irritation	Category	2	
Eye Irritation	Category	2B	
S.T.O.T. (S.E.)	Category	3	Specific Target Organ Toxicity - single exposure (narcotic effects)

HAZARD STATEMENTS:
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters the airway.
H315 Causes skin irritation.
H320 Causes eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness and dizziness.

PRECAUTIONARY STATEMENTS:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 2 of 11

- P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
P301 + P310 + P331 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.

Other Hazards: Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment.

3. Composition/Information on Ingredients

Component	CAS#	% by Weight
Stoddard Solvent	8052-41-3	20% to 25%
Synonyms: Mineral Spirits, Petroleum Solvent, Spotting Naphtha		

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. *First Aid Measures

- Eyes:** Check for and remove any contact lenses. Immediately flush eyes with large quantities of water and continue washing for 15 to 20 minutes. Seek Medical Attention if irritation or symptoms of overexposure persist.
- Skin:** Flush with fresh water. Remove contaminated clothing, including contaminated shoes, after flushing has begun. Wash skin with soap and water paying close attention to folds, crevices, creases and the groin area. Obtain medical attention if irritation persists. Launder clothing before reuse and discard contaminated shoes.
- Ingestion:** Do not induce vomiting! Do not give anything to drink. Wash mouth out with water. Call 911 or poison control center immediately. Keep person warm and quiet. Never give anything by mouth to an unconscious person.



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 3 of 11

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. If coughing, breathing difficulty or any other respiratory symptoms develop, seek medical attention at once. Extreme asthmatic reactions that may occur in sensitized persons can be life threatening. Asthmatic symptoms may develop and may be immediate or delayed up to several hours.

Important Symptoms / Effects, Acute & Delayed:

Irritation, drowsiness dizziness and narcosis. Irritant effects to eyes, nose, throat, and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Dermatitis. Kidney damage. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped.

Indication of Immediate Medical Attention, Special Treatment needed, if Necessary:

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General Information

If exposed or concerned, get medical attention / advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show SDS to physician. Wash contaminated clothing before re-use.

Note to Physicians: Provide SDS to physician. Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision. Skin: This compound is a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn. Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of the compound. Inhalation: Treatment is essentially symptomatic.

5. Fire Fighting Measures

Suitable Extinguishing Media:

FOAM, ALCOHOL FOAM, CO₂, DRY CHEMICAL, other Class B extinguishing agents.

Unsuitable extinguishing media:

Do not use water to extinguish.

Specific Hazards:

Flammable liquid may emit flammable and/or explosive vapors when mixed with ambient air. Vapors heavier than air may travel along the floor. May ignite when exposed to sparks, heat, flames, or oxidants. Hazardous decomposition of products by fire and high heat. Carbon Dioxide (CO₂), Carbon Monoxide (CO), oxides of nitrogen (NO_x), and other undetermined compounds. Unusual fire/explosion hazards closed container may forcibly rupture under extreme heat or when contents are contaminated with water (CO₂ formed). Use cold-water spray to cool fire-exposed containers to minimize the risk of rupture.

Special Protective Equipment and Precautions for Firefighters:

Personal protective equipment level C recommended. Firefighters should wear NFPA compliant



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 4 of 11

structural firefighting protective equipment, including Self-Contained Breathing Apparatus(SCBA) and NFPA compliant helmet, hood, boots and gloves. Remove containers from area if it can be done safely. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse.

6. Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate to safe area. Keep unnecessary personnel away. Local authorities should be advised if significant spills cannot be contained. Stay upwind of spill, and out of low areas. Ventilate closed spaces before entering. Avoid breathing vapor, gases, or mists. Wear protective clothing when handling spilled materials and/or damaged containers. Insure proper ventilation of fumes and vapors if it can be done safely. Material is **Flammable**. Review Firefighting Measures, Section 5, before proceeding with clean up. Extinguish all flames in the vicinity. Keep combustibles (wood, paper, oil, etc.) and hot surfaces away from spilled material. See section 8 for Personal Protective Equipment information.

Methods and Materials for Containment and Clean-up:

ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in the immediate area). Use explosion proof mechanical ventilation. Wear protective gear appropriate to the task. Absorb liquid with non-combustible, inert material such as earth or sand. Place absorbent material in non-leaking containers; seal tightly for proper disposal. Consult an expert on disposal of the material and ensure conformity to local disposal regulations. Also, see Section 15 for other regulatory information.

Small Spill: Eliminate all sources of ignition. Wear protective gear appropriate for the task. Prevent additional discharge of material and prevent liquid from entering sewers, watercourses or low areas. Dike spill area and add non-combustible absorbent material such as clay or sand to spilled liquid. Contain spill in smallest possible area. Recover as much product as possible (e.g. by vacuuming). Stop leak if it can be done without risk. Do not use combustible materials such as sawdust. Place absorbent material in non-leaking containers; seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination. Consult an expert on disposal of the material and ensure conformity to local disposal regulations. Also, see Section 15 for additional regulatory information.

Large Spill: Stop flow of material, if this may be done without risk. Eliminate all sources of ignition. Prevent additional discharge of material and prevent liquid from entering sewers, watercourses or low areas. Ventilate, if area is indoors, with non-mechanical ventilation or explosion proof mechanical ventilation. Wear protective gear appropriate for the task. Dike spill area and add absorbent material to spilled liquid. Do not use combustible materials such as sawdust. Place absorbent material in non-leaking containers; seal tightly for proper disposal. Isolate hazard area and restrict entry to emergency crew. Do not enter or stay in area unless monitoring indicates that it is safe to do so. Consult an expert on disposal of the material and ensure conformity to local disposal regulations. See Section 15 for other regulatory information.

Never return spills to original containers for re-use. Prevent entry into waterways, sewers, basements or confined areas. Stop leak if you can do so without risk. Dike the spilled material, where this is possible.

Environmental precautions:

If facility or operation has an "oil or hazardous substance contingency plan", activate its procedures. This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water. Should not be released into the environment. Do not allow material to contaminate ground water system. Prevent product from entering drains. Stay upwind and away from spill. Spilled material may be absorbed by an appropriate absorbent, and then handled in accordance with environmental regulations. Prevent spilled material from entering sewers, storm drains, other unauthorized treatment or drainage systems and natural waterways. Contact fire



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 5 of 11

authorities and appropriate federal, state and local agencies. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, contact the National Response Center at 1-800-424-8802. For highway or railways spills, contact Chemtrec at 1-800-424-9300.

7. Handling and Storage

Conditions for Safe Storage:

Store for flammable liquids required per OSHA 20 CFR 1910.106. No smoking in storage area. Keep all containers tightly closed when not in use. This material can accumulate static charge which may cause spark and become an ignition source. Use techniques to eliminate accumulated static charge when transferring materials. Make sure all equipment is grounded. The pressure in sealed containers can increase under the influence of heat. Store out of sunlight in a cool dry place, between 59° F and 77° F, with adequate explosion proof ventilation. Do not store near open flame, heat or other sources of ignition. Use only D.O.T. approved containers for storage, disposal, and transportation. Empty containers must meet 49 CFR 171.8 standards. Store separate from food products. Keep away from food, drink and animal feed and feeding areas. Keep out of the reach of children.

Electrostatic Hazard: Ground equipment to prevent accumulation of static charge. If you're pouring or transferring materials, containers must be bonded and grounded. Use spark resistant tools. Use only Department of Transportation approved containers. Additional information, regarding safe handling of products with static accumulation potential, can be ordered by contacting The American Petroleum Institute (API) for Recommended Proactive 2003, entitled "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" (American Petroleum Institute, 1720 L Street Northwest, Washington DC 2005) or The National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9109, Quincy, MA 02269-9101).

Incompatibilities: Avoid incompatible materials including Acids, Bases, Oxidizers.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits: Immediately Dangerous to Life or Health Concentrations (IDLH)

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Component	CAS No.	Type	Value
Stoddard Solvent	8052-41-3	PEL	500 ppm 2900 mg/m ³

U.S. OSHA Table Z-2

Component	CAS No.	8 Hr. avg.	Ceiling	Max Peak	Max Duration
Not Listed					

U.S. ACGIH Threshold Limit Values

Component	CAS No.	TWA	STEL
Stoddard Solvent	8052-41-3	100 ppm / 525 mg/m ³	No data

U.S. NIOSH Recommended Exposure Limit

Component	CAS No.	TWA/Ceiling (15 min)	IDLH
Stoddard Solvent	1330-20-7	350 mg/m ³ / 1,800mg/m ³	20,000 mg/m ³



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 6 of 11

Engineering Controls:

Use appropriate engineering controls such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment which performs satisfactorily and meets OSHA, NIOSH or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment. Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Personal Protective Equipment

Respiratory Protection:

When spraying, use a NIOSH approved organic vapor cartridge respirator or gas mask Class A1P2 (AS/NZS 1715) to keep airborne mists and vapor concentrations below the time weighted threshold limit values. In accordance with CFR 1910.134, when working in poorly ventilated and confined spaces, use an air purifying respirator for organic vapors and wet paint mist, a fresh-air supplying respirator, or a self-contained breathing apparatus (SCBA). Wear a dust or particle mask when sanding to prevent dust inhalation. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Skin Protection:

Avoid all skin contact. Depending on the conditions of use, cover as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Wear gloves, long sleeved shirts and pants. Impermeable chemical handling gloves for skin protection, such as nitrile type, and protective clothing as required, to prevent skin contact.

Eye Protection:

When directly handling liquid product, NIOSH approved ANSI Z87.1-1989 eye protection is required. Examples of eye protection include a chemical safety goggle, or chemical safety goggle in combination with a full-face shield when there is a greater risk of splash. Wear safety glasses, with splash guards, when pouring this material. Use chemical goggles when spraying this material. Contact lenses must not be worn when working with chemicals.

9. Physical and Chemical Properties

Appearance

Physical State:	Liquid
Color:	Colorless
Odor:	Mild Aromatic Odor
Odor Threshold:	Not Determined for this mixture.
pH:	Not Determined for this mixture.
Melting Point:	Not Determined for this mixture.
Freezing Point:	N/A
Boiling Point:	310-330 °F
Flash Point:	105-110 °F
Evaporation Rate:	N/A
Flammability (solid, gas):	Flammable liquid vapor
Upper / Lower Flammability or Explosive Limits	



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 7 of 11

Flammability Limit % – Lower:	Not Determined for this mixture.
Flammability Limit % – Upper:	Not Determined for this mixture.
Explosive Limit % – Lower:	1.0 %
Explosive Limit % – Upper:	7.5 %
Vapor Pressure:	0.62
Vapor Density:	Heavier than air
Relative Density (Specific Gravity):	0.90 – 0.96
Solubility(ies)	
Solubility in Water:	Non-Soluble.
Partition Coefficient	
n-octanol/water:	N/A
Auto Ignition Temperature:	Not Determined for this mixture.
Decomposition Temperature:	N/A
Viscosity (40° mm²/s):	Not Determined for this mixture.
Other Information	
Volatile Organic Compounds	
Coating:	(VOC) 1.11 – 1.92 lb/gl
Material:	(VOC) 1.11 - 1.92 lb/gl

10. Stability and Reactivity

Reactivity:

Not Available for this mixture.

Chemical Stability:

Stable under normal temperature conditions, recommended use, and recommended storage.

Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

Conditions to Avoid:

Avoid excessive heat, poor ventilation, corrosive atmospheres, excessive aging, sparks, open flames, heat, hot equipment, static electricity and other sources of ignition.

Incompatible Materials:

Strong acids, Acids. Alkalis, reducing and oxidizing materials.

Hazardous Decomposition Products: By Fire and High Heat - Carbon Dioxide (CO₂), Carbon Monoxide (CO), and other undetermined compounds may form during combustion.

11. Toxicological Information

Information on Likely Routes of Exposure

Ingestion:



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 8 of 11

May be fatal if swallowed and enters airway.

Inhalation:

Harmful if inhaled. May cause drowsiness or dizziness.

Skin Contact:

Harmful in contact with skin. Causes skin irritation.

Eye Contact:

Causes eye irritation.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics

Eye, nose & throat irritation, dizziness, dermatitis, and chemical pneumonitis. In animals: causes kidney damage.

Target organs: Eyes, Skin, Respiratory system, Central Nervous System, Kidneys.

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

Stoddard Solvent (CAS 8052-41-3)

Exposure at 2400 mg/m³ peak at 30 minutes: Irritation of the eyes, mucous membranes, cardio system, and upper respiratory tract.

Exposure at 610 mg/m³ for 6 hours: Damage to gastrointestinal system, muscular skeletal system, renal system, hepatic system.

Numerical Measures of Toxicity

Stoddard Solvent (CAS 8052-41-3)

Oral LD50 rat >5000 mg/kg

Dermal LD50 rabbit >3160 mg/kg

Hazardous Chemicals Lists

EPA: Not listed

IARC: Stoddard Solvent (CAS 8052-41-3)
Group 3 - Not classifiable as to its carcinogenicity to humans.

OSHA PEL: Stoddard Solvent (CAS 8052-41-3)
29 CFR 1910.1000 Table Z-1 - 500 ppm TWA

NTP: No components listed.

12. Ecological Information

Environmental Fate: No data is available on the adverse effects of this mixture on the environment. This product should be considered harmful to fish and algae upon immediate exposure. If this product is spilled, caution should be exercised to keep this product from entering any type of a waterway or storm sewer. When released into the soil, this material may leach into the groundwater. When released into water, acidity may be readily reduced by natural water hardness minerals.

Environmental Toxicity: This product contains Stoddard Solvent (CAS 8052-41-3) which may cause oxygen



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 9 of 11

depletion in waterways; potentially toxic to water ecosystems; may be hazardous to aquatic life; may contribute to smog. not a DOT marine pollutant.

Marine Pollutant: Not considered a DOT marine pollutant.

Stoddard Solvent (CAS 8052-41-3)

Freshwater Invertebrate (Daphnia magna) EiL_{50} 1.62 mg/L - 21 day

Freshwater alga (Pseudokirchneriella subcapitata) NOELR(b,r) = 0.76 (mg/L) - 96-hr

Chemical Fate Information: Not Determined for this mixture.

Other Adverse Effects: Not Determined for this mixture.

13. Disposal Considerations

Waste Disposal Method: Collect absorbent material and /or spilled liquid mixture into metal containers and add enough water to cover. Consult local, state & federal hazardous waste regulations before disposing into approved hazardous waste disposal facilities. This material has been tested and found to have a flash point below 140 °F. If discarded, this material and its container, should be treated as hazardous waste based on the ignitable characteristic as defined under Federal RCRA Regulations 40 CFR 261. Disposal of this material or its container, requires compliance with applicable labeling, packaging, and record keeping standards. Extreme care should be taken to ensure that it is disposed of only in a facility permitted for disposal of hazardous waste. For further information, contact your state, local, or Federal Government agency.

RCRA: No ingredients listed as a hazardous waste according to RCRA 40 CFR Parts 261.3 U series and P series.

Contaminated Materials: Eliminate ignition sources and provide good ventilation. Place contaminated material in non-leaking containers; seal tightly for proper disposal. See Section 15 for additional regulatory information.

14. Transport Information

Domestic DOT, International IMO

Proper Shipping Name: Paint

Transportation Hazard Class: 3

Packaging Group: II

United Nations Identification Number: UN-1263

Environmental Hazards: Not considered a DOT marine pollutant.

Bulk Transport: Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code.

No information available.

Special Precautions: Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory Information



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 10 of 11

U.S. Federal Regulations:

TSCA	Section 12(b) Export Notification (40 CFR 707, Subpart. D) Not listed
OSHA:	Specifically Regulated Substances (29 CFR 1910.1001-1050, subpart Z). Stoddard Solvent (CAS 8052-41-3)
CERCLA:	Hazardous Substance List (40 CFR 302.4) Not listed
SARA	Hazard Category Section 304 Indicates toxic chemical(s) subject to the reporting requirements of Title III and of CFR 372. Not listed Hazard Category Section 313 Indicates toxic chemical(s) subject to the reporting requirements of Title III and of CFR 372. Not listed SARA Hazard Category Section 311/312 Indicates toxic chemical(s) subject to the reporting requirements of Title III and of CFR 372. Stoddard Solvent (CAS 8052-41-3) Fire hazard Acute health hazard Chronic health hazard
Clean Air Act	Section 112 Hazardous Air Pollutants (HAPs) List Not listed Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not listed

State Regulations

Right to know Hazardous substance list.

Massachusetts:	Stoddard Solvent (CAS 8052-41-3)
New York:	Not listed.
New Jersey:	Stoddard Solvent (CAS 8052-41-3)
Pennsylvania:	Stoddard Solvent (CAS 8052-41-3)
California Prop. 65:	Safe Drinking Water and Toxic Enforcement Act of 1986: chemicals known to the state to cause cancer or reproductive toxicity. No Significant Risk Level: None of the chemicals in this product are listed.

International Regulations

Canadian NPRI / WHMIS:	Canadian Environmental Extremely Hazardous Substances Material causing immediate and serious toxic effects: Right to know Hazardous substance list. Stoddard Solvent (CAS 8052-41-3) B3 Combustible liquid D2B Toxic materials
-------------------------------	--



SAFETY DATA SHEET

STANDARD PAINTS, INC.
Transparent Fence Stain Multi Color
Date Printed: 4/21/17
Date Revised: 1/9/17
Page 11 of 11

16. Other Information

Caution: Consult Safety Data Sheet prior to use. For Industrial Use Only. Contact the manufacturer with any product related questions.

Prepared by: Standard Paints, Inc.

Information Contact:

Compliance Manager
Standard Paints, Inc.
940 S. 6th Avenue
Mansfield, Texas 76063

Manufacturer Disclaimer: The information and recommendations contained herein are provided in good faith and are accurate to the best of our knowledge as of the date of preparation. We do not suggest or guarantee, that any hazards listed herein are the only ones which exist and we make no representation of its completeness or accuracy. Standard Paints, Inc. makes no warranty or representations of any kind, expressed or implied, concerning the safe use of this material in your process or in combination with other substances and/or materials. User has the sole responsibility to determine the suitability of the materials for any use, the manner of use contemplated and should consider this data only as supplement to other information gathered by them. User must make independent determinations of suitability and completeness of information from all sources to insure proper use and disposal of this product, the safety and health of employees and customers and the protection of the environment. User must meet all applicable safety and health standards. Since the use of this information and conditions of the use of the product are not within our control we make no warranty or representations, of any kind, expressed or implied, including, but not limited to, those of merchantability or fitness for a particular purpose with respect to this information or to the product it describes. We do not accept liability for any loss or damage, that may occur from the use of this information nor do we offer warranty against patent infringement.